

BIMETAL THERMOMETERS WITH TEMPERATURE TRANSMITTERS BACK CONNECTED

WSSPZ-W CORE EXTRACTABLE BIMETAL RTD INTEGRAL TEMPERATURE TRANSMITTER

Dial Diameter of 2.4" (60 mm)

Thread M16x1.5

WSSPZ-301W: removable outside thread

WSSPZ-302W: removable inside thread

WSSPZ-303W: fixed thread

Flange

WSSPZ-304W: flange, please identify

Dial Diameter of 3.9" (100 mm)

Thread M27x2

WSSPZ-401W: removable outside thread

WSSPZ-402W: removable inside thread

WSSPZ-403W: fixed thread

Flange

WSSPZ-404W: flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

WSSPZ-501W: removable outside thread

WSSPZ-502W: removable inside thread

WSSPZ-503W: fixed thread

Flange

WSSPZ-504W: flange, please identify



WSSK(E)Z -W CORE EXTRACTABLE BIMETAL THERMOCOUPLE INTEGRAL TRANSMITTER

K: With K styled sheathed thermocouple NiCr-NiSi

E: With E styled sheathed thermocouple NiCr-NiCu

Dial Diameter of 2.4" (60 mm)

Thread M16x1.5

WSSK(E)Z -301W: removable outside thread

WSSK(E)Z -302W: removable inside thread

WSSK(E)Z -303W: fixed thread

Flange

WSSK(E)Z- 304W: flange, please identify

Dial Diameter of 3.9" (100 mm)

Thread M27x2

WSSK(E)Z-401W: removable outside thread

WSSK(E)Z-402W: removable inside thread

WSSK(E)Z-403W: fixed thread Flange

WSSK(E)Z-404W: flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

WSSK(E)Z-501W: removable outside thread

WSSK(E)Z-502W: removable inside thread

WSSK(E)Z-503W: fixed thread

Flange

WSSK(E)Z-504W: flange, please identify