

BIMETAL THERMOMETER WITH TEMPERATURE TRANSMITTERS BOTTOM CONNECTED

WSSPZ-W CORE EXTRACTABLE BIMETAL RTD INTEGRAL TEMPERATURE TRANSMITTER

Dial Diameter of 2.4" (60 mm)

Thread M16x1.5

WSSPZ-311W: removable outside thread

WSSPZ-312W: removable inside thread

WSSPZ-313W: fixed thread

Flange

WSSPZ-314W: flange, please identify

Dial Diameter of 3.9" (100 mm)

Thread M27x2

WSSPZ-411W: removable outside thread

WSSPZ-412W: removable inside thread

WSSPZ-413W: fixed thread

Flange

WSSPZ-414W: flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

WSSPZ-511W: removable outside thread

WSSPZ-512W: removable inside thread

WSSPZ-513W: fixed thread

Flange

WSSPZ-514W: flange, please identify

WSSK(E)Z -W CORE EXTRACTABLE BIMETAL THERMOCOUPLE INTEGRAL TRANSMITTER

K: With K styled sheathed thermocouple NiCr-NiSi

E: With E styled sheathed thermocouple NiCr-NiCu

Dial Diameter of 2.4" (60 mm)

Thread M16x1.5

WSSK(E)Z -311W: removable outside thread

WSSK(E)Z -312W: removable inside thread

WSSK(E)Z -313W: fixed thread

Flange

WSSK(E)Z- 314W: flange, please identify

Dial Diameter of 3.9" (100 mm)

Thread M27x2

WSSK(E)Z-411W: removable outside thread

WSSK(E)Z-412W: removable inside thread

WSSK(E)Z-413W: fixed thread Flange

WSSK(E)Z-414W: flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

WSSK(E)Z-511W: removable outside thread

WSSK(E)Z-512W: removable inside thread

WSSK(E)Z-513W: fixed thread

Flange

WSSK(E)Z-514W: flange, please identify