

**GEAR STYLE BIMETAL TEMPERATURE WITH TRANSMITTERS  
AND ELECTRO SWITCH  
ADJUSTABLE ANGLE**

**WSSXPZ-W GEAR STYLE BIMETAL RTD INTEGRAL TEMPERATURE TRANSMITTER WITH  
ELECTRICAL SWITCH**

---

Dial Diameter of 2.4" (60 mm)

Thread M16x1.5

**(1-3)** indicates with:

1. Upper & Lower Setting
  2. Dual Upper Limit Setting
  3. Dual Lower Limit Setting
- Please specify when ordering.

**WSSXPZ-481W(1-3):** removable outside thread

**WSSXPZ-482W(1-3):** removable inside thread

**WSSXPZ-483W(1-3):** fixed thread

Flange

**WSSXPZ-484W(1-3):** flange, please identify

**Picutres**

**WSSXK(E)Z -W GEAR STYLE BIMETAL THERMOCOUPLE INTEGRAL TEMPERATURE  
TRANSMITTER WITH ELECTRICAL SWITCH**

---

Dial Diameter of 2.4" (60 mm)

Thread M16x1.5

**K:** With K styled sheathed thermocouple NiCr-NiSi

**E:** With E styled sheathed thermocouple NiCr-NiCu

**(1-3)** indicates with:

1. Upper & Lower Setting
  2. Dual Upper Limit Setting
  3. Dual Lower Limit Setting
- Please specify when ordering.

**WSSXK(E)Z-481W(1-3):** removable outside thread

**WSSXK(E)Z-482W(1-3):** removable inside thread

**WSSXK(E)Z-483W(1-3):** fixed thread

Flange

**WSSXK(E)Z-484W(1-3):** flange, please identify