

## **FLAME-PROOF BIMETAL THERMOMETERS BACK CONNECTED**

### **WSS-B CORE EXTRACTABLE PROTECTIVE FLAME PROOF BIMETAL THERMOMETER**

---

Dial Diameter of 3.94" (100 mm)

Thread M27x2

**WSS-401B:** removable outside thread

**WSS-402B:** removable inside thread

**WSS-403B:** fixed thread

Flange

**WSS-404B:** flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

**WSS-501B:** removable outside thread

**WSS-502B:** removable inside thread

**WSS-503B:** fixed thread

Flange

**WSS-504B:** flange, please identify



### **WSSP-B CORE EXTRACTABLE PROTECTIVE FLAME PROOF BIMETAL RTD INTEGRAL THERMOMETER**

---

Dial Diameter of 3.94" (100 mm)

Thread M27x2

**WSSP-401B:** removable outside thread

**WSSP-402B:** removable inside thread

**WSSP-403B:** fixed thread

Flange

**WSSP-404B:** flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

**WSSP-501B:** removable outside thread

**WSSP-502B:** removable inside thread

**WSSP-503B:** fixed thread

Flange

**WSSP-504B:** flange, please identify

### **WSSK(E)-B CORE EXTRACTABLE PROTECTIVE FLAME PROOF BIMETAL THERMOCOUPLE INTEGRAL THERMOMETER**

---

**K:** With K styled sheathed thermocouple NiCr-NiSi

**E:** With E styled sheathed thermocouple NiCr-NiCu

Dial Diameter of 3.94" (100 mm)

Thread M27x2

**WSSK(E)-401B:** removable outside thread

**WSSK(E)-402B:** removable inside thread

**WSSK(E)-403B:** fixed thread

Flange

**WSSK(E)-404B:** flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

**WSSK(E)-501B:** removable outside thread

**WSSK(E)-502B:** removable inside thread

**WSSK(E)-503B:** fixed thread

Flange

**WSSK(E)-504B:** flange, please identify