

FLAME-PROOF BIMETAL THERMOMETER WITH TEMPERATURE TRANSMITTERS
TYPE: BACK CONNECTED

WSSPZ-B CORE EXTRACTABLE PROTECTIVE FLAME PROOF BIMETAL RTD INTEGRAL TEMPERATURE TRANSMITTER

Dial Diameter of 3.94" (100 mm)

Thread M27x2

WSSPZ-401B: removable outside thread

WSSPZ-402B: removable inside thread

WSSPZ-403B: fixed thread

Flange

WSSPZ-404B: flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

WSSPZ-501B: removable outside thread

WSSPZ-502B: removable inside thread

WSSPZ-503B: fixed thread

Flange

WSSPZ-504B: flange, please identify



WSSK(E)Z-B CORE EXTRACTABLE FLAME PROOF BIMETAL THERMOCOUPLE INTEGRAL TEMPERATURE TRANSMITTER

K: With K styled sheathed thermocouple NiCr-NiSi

E: With E styled sheathed thermocouple NiCr-NiCu

Dial Diameter of 3.94" (100 mm)

Thread M27x2

WSSK(E)Z-401B: removable outside thread

WSSK(E)Z-402B: removable inside thread

WSSK(E)Z-403B: fixed thread

Flange

WSSK(E)Z-404B: flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

WSSK(E)Z-501B: removable outside thread

WSSK(E)Z-502B: removable inside thread

WSSK(E)Z-503B: fixed thread

Flange

WSSK(E)Z-504B: flange, please identify