

FLAME-PROOF BIMETAL THERMOMETERS BACK CONNECTED

WSS-B CORE EXTRACTABLE PROTECTIVE FLAME PROOF BIMETAL THERMOMETER

Dial Diameter of 3.94" (100 mm)

Thread M27x2

WSS-401B: removable outside thread

WSS-402B: removable inside thread

WSS-403B: fixed thread

Flange

WSS-404B: flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

WSS-501B: removable outside thread

WSS-502B: removable inside thread

WSS-503B: fixed thread

Flange

WSS-504B: flange, please identify



WSSP-B CORE EXTRACTABLE PROTECTIVE FLAME PROOF BIMETAL RTD INTEGRAL THERMOMETER

Dial Diameter of 3.94" (100 mm)

Thread M27x2

WSSP-401B: removable outside thread

WSSP-402B: removable inside thread

WSSP-403B: fixed thread

Flange

WSSP-404B: flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

WSSP-501B: removable outside thread

WSSP-502B: removable inside thread

WSSP-503B: fixed thread

Flange

WSSP-504B: flange, please identify

WSSK(E)-B CORE EXTRACTABLE PROTECTIVE FLAME PROOF BIMETAL THERMOCOUPLE INTEGRAL THERMOMETER

K: With K styled sheathed thermocouple NiCr-NiSi

E: With E styled sheathed thermocouple NiCr-NiCu

Dial Diameter of 3.94" (100 mm)

Thread M27x2

WSSK(E)-401B: removable outside thread

WSSK(E)-402B: removable inside thread

WSSK(E)-403B: fixed thread

Flange

WSSK(E)-404B: flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

WSSK(E)-501B: removable outside thread

WSSK(E)-502B: removable inside thread

WSSK(E)-503B: fixed thread

Flange

WSSK(E)-504B: flange, please identify