

**FLAME-PROOF BIMETAL THERMOMETER WITH TEMPERATURE TRANSMITTERS**  
**TYPE: BACK CONNECTED**

**WSSPZ-B CORE EXTRACTABLE PROTECTIVE FLAME PROOF BIMETAL RTD INTEGRAL TEMPERATURE TRANSMITTER**

---

Dial Diameter of 3.94" (100 mm)

Thread M27x2

**WSSPZ-401B:** removable outside thread

**WSSPZ-402B:** removable inside thread

**WSSPZ-403B:** fixed thread

Flange

**WSSPZ-404B:** flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

**WSSPZ-501B:** removable outside thread

**WSSPZ-502B:** removable inside thread

**WSSPZ-503B:** fixed thread

Flange

**WSSPZ-504B:** flange, please identify



**WSSK(E)Z-B CORE EXTRACTABLE FLAME PROOF BIMETAL THERMOCOUPLE INTEGRAL TEMPERATURE TRANSMITTER**

---

**K:** With K styled sheathed thermocouple NiCr-NiSi

**E:** With E styled sheathed thermocouple NiCr-NiCu

Dial Diameter of 3.94" (100 mm)

Thread M27x2

**WSSK(E)Z-401B:** removable outside thread

**WSSK(E)Z-402B:** removable inside thread

**WSSK(E)Z-403B:** fixed thread

Flange

**WSSK(E)Z-404B:** flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

**WSSK(E)Z-501B:** removable outside thread

**WSSK(E)Z-502B:** removable inside thread

**WSSK(E)Z-503B:** fixed thread

Flange

**WSSK(E)Z-504B:** flange, please identify