

## **FLAME-PROOF BIMETAL THERMOMETER WITH TEMPERATURE TRANSMITTERS**

**TYPE: BOTTOM CONNECTED**

### **WSSPZ-B CORE EXTRACTABLE PROTECTIVE FLAME PROOF BIMETAL RTD INTEGRAL TEMPERATURE TRANSMITTER**

---

Dial Diameter of 3.94" (100 mm)

Thread M27x2

**WSSPZ-411B:** removable outside thread

**WSSPZ-412B:** removable inside thread

**WSSPZ-413B:** fixed thread

Flange

**WSSPZ-414B:** flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

**WSSPZ-511B:** removable outside thread

**WSSPZ-512B:** removable inside thread

**WSSPZ-513B:** fixed thread

Flange

**WSSPZ-514B:** flange, please identify



### **WSSK(E)Z-B CORE EXTRACTABLE FLAME PROOF BIMETAL THERMOCOUPLE INTEGRAL TEMPERATURE TRANSMITTER**

---

**K:** With K styled sheathed thermocouple NiCr-NiSi

**E:** With E styled sheathed thermocouple NiCr-NiCu

Dial Diameter of 3.94" (100 mm)

Thread M27x2

**WSSK(E)Z-411B:** removable outside thread

**WSSK(E)Z-412B:** removable inside thread

**WSSK(E)Z-413B:** fixed thread

Flange

**WSSK(E)Z-414B:** flange, please identify

Dial Diameter of 5.9" (150 mm)

Thread M27x2

**WSSK(E)Z-511B:** removable outside thread

**WSSK(E)Z-512B:** removable inside thread

**WSSK(E)Z-513B:** fixed thread

Flange

**WSSK(E)Z-514B:** flange, please identify